

Trash Pump

TP08



SPECIFICATIONS

| ITEM | U.S.A. | METRIC |
|-----------------------|--|-----------|
| Capacity | 800 gpm | 3,028 lpm |
| Weight | 59 lbs | 26.7 kg |
| Height (over handle) | 16.5 in. | 42 cm |
| Length | 19 in. | 48.3 cm |
| Width | 15 in. | 38.1 cm |
| Pressure | 2,000 psi | 140 bar |
| Flow Range | 7-9 gpm | 26-34 lpm |
| Maximum Flow | 9 gpm | 34 lpm |
| Porting | #10 SAE (Press.) #12 SAE (Ret) | |
| Connect Size and Type | 1/2 in. Male Pipe (Press.) 3/4 in. Male Pipe (Ret) | |
| Discharge Diameter | 4 in. Camlock | |
| Inlet Diameter | 4 in. | 100 mm |

The Stanley **TP08** Trash Pump is a light-weight, heavy duty pump capable of pumping high volumes of water, sand slurries, gravel, sludge and solids up to 3 in./75 mm in diameter. The **TP08** is submersible, self priming and can run dry without damage to the motor, bearings or impeller.

The **TP08** has been designed to get the most from an HTMA Type II hydraulic circuit. Using only 9 gpm/34 lpm of hydraulic flow, the **TP08** will pump over 800 gpm/3,028 lpm at a 10 ft/2.54 m head. The free-flow impeller and 4 in./ 100 mm inlet and outlet combine to make the **TP08** one of the most efficient pumps in the business.

Weighing only 59 lbs/27 kg and with its convenient handle, the **TP08** can easily be

handled by one operator. The **TP08** and the Stanley HP28 Power Unit make a powerful, portable team for high volume de-watering and trash pump applications.

The heavy-duty construction of the **TP08** features a fabricated, all steel volute and abrasion resistant cast iron impeller. The volute uses replaceable UHMW polyeth-ylene wear plates to reduce wear and extend pump life. The heavy-duty Stanley HYREVZ™ hydraulic motor is self-lubricating.

ORDERING INFORMATION

ORDER NO.


DESCRIPTION

TP08013


4 in. Trash Pump, 800 gpm/3028 lpm

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.



TP08 PERFORMANCE CHART



All Stanley Hydraulic Tools, Parts, Accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult Stanley Hydraulic Tools.

Call the Stanley Hydraulic Tools dealer nearest you...

Stanley Hydraulic Tools

3810 SE Naef Road
Milwaukie, OR 97267-5698

Tel 503-659-5660
Fax 503-652-1780

