

DL07 DRILL

STANLEY®



FEATURES:

- Instant reverse for high reliability and efficiency in all types of drilling applications.
- Dual-position Assist Handle on some models provides increased control and performance on tough drilling jobs.
- The new over-sized reversing spool is protected by heavy-duty wiper seals. These wiper seals clean away dirt as the spool is moved.
- Ideal for drilling holes in wood, metal and masonry

DL07 DRILL IS IDEAL FOR DRILLING HOLES IN WOOD, METAL AND MASONRY - THE POWER OF HYDRAULICS

SPECIFICATIONS

DL07		
Capacity	1/2 in. Chuck	
	12 mm Chuck	
Weight*	6 lb	
	2.7 kg	
Length*	9 in.	
	22.90 cm	
Ports	-8 SAE O-Ring	
Motor	Stanley Hyrevz™ Gear	
System Type	Open Center/Closed Center	
Maximum Flow	12 gpm	
	45 lpm	
Torque		
	U.S.A	Metric
4 ft lb @ 500 psi		.5 Nm @ 35 bar
9 ft lb @ 1000 psi		1.2 Nm @ 70 bar
14 ft lb @ 1500 psi		1.9 Nm @ 105 bar
19 ft Lb @ 2000 psi		2.6 Nm @140 bar
DRILL SPEED/HYDRAULIC FLOW		
350 rpm @ 3 gpm		11.3 lpm
475 rpm @ 4 gpm		15 lpm
750 rpm @ 6 gpm		23 lpm
1000 rpm @ 8 gpm		70-140 bar
1250 rpm @ 10 gpm		7-9 gpm



DL07 DRILL

STANLEY®

ORDERING INFORMATION

MODEL	PART NO.	DESCRIPTION
DL07	DL07550	OC/CC*, Dual Spool, Trigger Guard, Assist Handle, 1/2 in. Chuck, Couplers, No Hose Whips
	DL0755001	OC/CC*, Dual Spool, Trigger Guard, Assist Handle, 1/2 in. Chuck, Couplers, No Hose Whips, CE
	DL07652	OC/CC*, Dual Spool, Trigger Guard, 1/2 in. Chuck, Assist Handle, Hose Whips, No Couplers, Underwater Use

ACCESSORIES

ITEM NO.	DESCRIPTION
	Carbide Tipped Augers with 7/16 in. Shank
27850	9/16 in. Dia., 8 in. Twist, 12 in. OAL
27851	11/16 in. Dia., 8 in. Twist, 12 in. OAL
27852	13/16 in. Dia., 8 in. Twist, 12 in. OAL
27855	9/16 in. Dia., 12 in. Twist, 16 in. OAL
27856	11/16 in. Dia., 12 in. Twist, 16 in. OAL
27857	13/16 in. Dia., 12 in. Twist, 16 in. OAL
27858	15/16 in. Dia., 12 in. Twist, 16 in. OAL
27859	1-1/16 in. Dia., 12 in. Twist, 16 in. OAL
27860	9/16 in. Dia., 18 in. Twist, 22 in. OAL

ITEM NO.	DESCRIPTION
	Carbide Tipped Augers with 7/16 in. Shank
27861	11/16 in. Dia., 18 in. Twist, 22 in. OAL
27862	13/16 in. Dia., 18 in. Twist, 22 in. OAL
27863	15/16 in. Dia., 18 in. Twist, 22 in. OAL
27864	1-1/16 in. Dia., 18 in. Twist, 22 in. OAL
27865	11/16 in. Dia., 32 in. Twist, 36 in. OAL
27869	13/16 in. Dia., 36 in. Twist, 48 in. OAL
32400	13/16 in. Dia., 15 in. Twist, 18 in. OAL

OAL = Over All Length

WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

