

GT18 POWER UNIT

January 2015



The GT18 power unit is designed for continuous duty operation of any hydraulic tool in the Type I or Type II category or wherever 8 gpm at 2000 psi of hydraulic power is required. World class cooling puts the GT18 far ahead of all other power units on the market.

Features:

- Type I or Type II hydraulic circuit with superior cooling
- Electronically controlled engine speed - provides 5 or 8 gpm
- Auto idle feature - lower fuel consumption and less noise
- Tool circuit lockout during engine start-up - safety feature
- Quartz hour meter on control panel - records engine run time
- Lift and latch handle with fold up side handles
- 35 - AH sealed, non spillable, no maintenance battery located in covered compartment
- Electric start engine has pressure lubrication system, low engine oil shut down and spin on oil filter
- In tank hydraulic filter with dipstick and easy access filter replacement

SPECIFICATIONS

Output Capacity	5 or 8 gpm / 20 or 30 lpm
Pressure	2000 psi / 140 bar
Circuit Type	Open Center
Hydraulic Reservoir Capacity	3 Gallons / 11 Liters
Couplers	HTMA Flush Face
Fuel Tank Capacity	5.5 Gallons / 20.8 Liters
Engine	Briggs & Stratton 18 hp Vanguard OHV
Weight	330 lbs / 150 kg
Length	35 in. / 89 cm
Width	21.5 in. / 54.6 cm
Height	29 in. / 73.7 cm
Heat Rejection	5 hp



GT18 POWER UNIT

January 2015

ORDERING INFORMATION

Part No.	Description
Gt18B01	5 or 8 gpm Briggs & Stratton 18 hp, CE
GT18B02	5 or 8 gpm Briggs & Stratton 18 hp

Accessories	Description
31848	Dual Hose, 50 ft x 1/2 in. with Couplers
31972	Dual Hose, 25 ft x 1/2 in. with Couplers
58633	Twinned Hose, 25 ft x 1/2 in. with Couplers
58634	Twinned Hose, 50 ft x 1/2 in. with Couplers
33212	Weather Cover
13360	Hose Basket Conversion Kit



WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specifications and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.